

SPECIFICATION



In-Touch™ HD White Board Display

Model	Pen Touch			Finger Touch		
	IT-6001P	IT-6002P	IT-7202P	IT-6001F	IT-6002F	IT-7202F
Size	60"	60"	72"	60"	60"	72"
Resolution	1280x720 (720P)		1920x1080 (1080P)	1280x720 (720P)		1920x1080 (1080P)
Display Technology	0.45" TypexDLP™		0.65" TypexDLP™	0.45" TypexDLP™		0.65" TypexDLP™
Reaction Time	16μs					
Contrast	>1200 : 1					
Brightness	>500nits	>900nits	>700nits	>500nits	>900nits	>700nits
View Angle (Horizontal)	≤160°					
View Angle (vertical)	≤80°					
Input signal	HDMI×2,YPbPr×2,S-Video×1,CVBS×2,VGA×1,*RF×1(Option)					
Audio Amplifier	15w×2					
Power Requirement	AC 100-220V/50-60Hz					
Power Consumption	230W		260W	230W		260W
Power Standby	Less1W					
Lamp Type	150W		180W	150W		180W
Lamp Life	8000Hrs		6000Hrs	8000Hrs		6000Hrs
Dimension (mm)	1371×976×354	1371×976×354	1637×1144×421	TBD		
Net Weight	51Kg	51Kg	73Kg	TBD		
Touch Method	Pen Touch			Finger Touch		
Connection Port/Effects Distant	USB/5M					
White Board Material	Tempered Glass					
Attachment	USB, Driver, White Board Software					

Multi In-Touch™ Display Platform

Model	Multi Touch™ Display Platform			
	IT-5001M(T/L)	IT-6001M(T/L)	IT-6002M(T/L)	IT-7202M(T/L)
Size	50"	60"	60"	72"
Resolution	1280x720 (720P)		1920x1080 (1080P)	
Display Technology	0.45" TypexDLP™		0.65" TypexDLP™	
Reaction Time	16μs			
Contrast	>1200 : 1			
Brightness	>700nits	>500nits	>900nits	>700nits
View Angle (Horizontal)	≤160°			
View Angle (vertical)	≤80°			
Input Signal	HDMI×2,YPbPr×2,S-Video×1,CVBS×2,VGA×1			
Audio Amplifier	15w×2			
Power Requirement	AC 100-220V/50-60Hz			
Power Consumption	230W		260W	
Power Standby	低于1W			
Lamp Type	150W		180W	
Lamp Life	8000Hrs		6000Hrs	
Dimensions (mm)	1198×866×317	1419×998×362	1419×998×362	1685×1164×433
Net Weight	42kg	58kg	58kg	80kg
Connection Port	USB 2.0	IEEE1394a 6pin	IEEE1394a 6pin	IEEE 1394a 6pin
Touch Point	3 points	32 Points		
White Board Material	Tempered Glass			

DLP Video Wall

Model	1×2 Video Wall		2×1 Video Wall	
	DW2-6002PA	DW2-7202PA	DW2-6002PB	DW2-7202PB
Size	60"	72"	60"	72"
Resolution	1920x1080 (1080P)		1920x1080 (1080P)	
Display Technology	0.65" TypexDLP™		0.65" TypexDLP™	
Reaction Time	16μs		16μs	
Contrast	>1200:1		>1200:1	
Brightness	>700nits		>700nits	
View Angle (Horizontal)	≤160°		≤160°	
View Angle (vertical)	≤80°		≤80°	
Video Wall Input	VGA,HDMI		VGA,HDMI	
Audio Output	1way		1way	
Power Requirement	AC 100-220V/50-60Hz		AC 100-220V/50-60Hz	
Power Consumption	230W	260W	230W	260W
Power Standby	Less1W		Less1W	
Lamp Type	150W	180W	150W	180W
Lamp Life	8000Hrs	6000Hrs	8000Hrs	6000Hrs
Exterior Dimension (mm)	2688×918×445	3236×1081×487	1344×1836×445	1618×2162×487
Net Weight (Kg)	160	200	160	200
In-Touch Method	Pen Touch			
Connection Port/ Effect Distant	USB/5M			
Whiteboard Material	Tempered Glass			
Attachment	USB, Drive, White Board Software			

Distributor

nLighten in Shanghai

Building 17, No.1515, GuMei Rd.,
Xu-Hui District, Shanghai ,200233, China
TEL : 86-21-53022229
FAX : 86-21-54451277

nLighten in Taiwan

No.568, Fusing 3rd Rd., Gueishan Township,
Taoyuan County(333), Taiwan, R.O.C.
TEL : 886-3-3277288
FAX : 886-3-3277622

nLighten in USA

47800 Fremont Blvd.,Fremont,
CA 94538,U.S.A.
TEL : 1-510-4450100
FAX : 1-510-4451678

nLighten in Europe

Suite 3 Swallow Court Devonshire
Gate Tiverton EX 16 7EJ England
TEL : 44-0-1884-849300
FAX : 44-0-1884-849240